

# C/S GRANULAR™

## 30-50 MESH GRANULAR BENTONITE

Certified to  
NSF/ANSI 60

# CETCO® CRUMBLES # 8

Formerly VOLCLAY CRUMBLES

## 8-20 MESH GRANULAR BENTONITE

### DESCRIPTION

C/S GRANULAR and CETCO CRUMBLES are granular bentonite products composed of polymer-free, dried bentonite clay in various mesh sizes. CETCO CRUMBLES are coarser in size than C/S GRANULAR. C/S C/S GRANULAR and CETCO CRUMBLES are certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

### RECOMMENDED USE

May be used as casing seal, hole abandonment material, and for sealing earthen structures.

### CHARACTERISTICS

- Less than 10% moisture
- Provide a positive seal
- Re-hydrates
- Will not shrink or crack

### MIXING AND APPLICATION

Grouting Material	One bag CETCO CRUMBLES to 24 gallons water and 8 ounces ACCU-VIS
Dry Shallow Abandonment	Pour required amount directly down borehole; hydrate with freshwater
Earthen Structure Seal	Normal treatment is 1-2 pounds per ft <sup>2</sup> depending on soil type

### BULK DENSITY

65 lbs/ft<sup>3</sup>

### PACKAGING

50 lb multi-wall bags; 48 per pallet. All pallets are plastic-wrapped.